

AMENDMENTS TO THE CLAIMS

Please accept amended claims 1-3, 13, 14 and 25 as follows:

1. (Currently Amended) A method for augmented reality guided instrument positioning, comprising the steps of:

displaying a real view of an environment including an instrument;

determining a ~~graphics guide~~ preferred path for positioning of said instrument;

marking the preferred path with a graphics guide; and

augmenting the real view with a rendering of the graphics guide such that a ~~transparency of~~ at least one portion of the graphics guide is transparent with respect to other portions of the graphics guide to provide a substantially unobstructed view through the at least one portion of the graphics guide to at least a portion of the instrument; ~~modulated in and out of an augmented view repeatedly over a predefined time interval, independent of a change in a view of the graphics guide~~

aligning the instrument with the graphics guide so that the instrument appears in a same location as the graphics guide in the augmented view, and when properly aligned, at least a portion of the instrument is visible through the at least one transparent portion of the graphics guide; and

inserting the instrument in the graphics guide.

2. (Currently Amended) The method according to claim 1, wherein ~~said rendering step comprises the step of varying the transparency of the at least one~~ said rendering includes a modulation of the graphics guide's transparency along the length of the graphics guide, so that a plurality of portions of the graphics guide appear transparent with respect to other portions of the graphics guide along the length of the graphics guide to provide a substantially unobstructed view through the at least one plurality of transparent portions of the graphics guide to a plurality of portions of the instrument once the instrument has been correctly aligned with the graphics guide.

3. (Currently Amended) The method according to claim 1, wherein said rendering step comprises the step of varying the transparency of the at least one portion of the graphics guide during ~~the~~ pre-defined time intervals to provide a substantially unobstructed view

through the at least one portion of the graphics guide to at least a portion of the instrument during the pre-defined time intervals.

4. (Previously Presented) The method according to claim 1, wherein said rendering step comprises the step of sequentially varying the transparency of each of a plurality of portions of the graphics guide during at least one pre-defined time interval to provide a substantially unobstructed view through each of the plurality of portions to at least a portion of the instrument as the transparency of each of the plurality of portions is varied during the at least one pre-defined time interval.

5. (Original) The method according to claim 4, wherein the plurality of portions are consecutive.

6. (Previously Presented) The method according to claim 1, wherein said rendering step comprises the step of varying the transparency of the at least one portion of the graphics guide such that the at least one portion repeatedly switches between transparent and less transparent.

7. (Previously Presented) The method according to claim 1, wherein said determining step comprises the step of constructing the graphics guide as a line, and said rendering step comprises the step of modulating the transparency of the line with respect to time so that the line repeatedly fades in and out of view to provide a substantially unobstructed view of the instrument when the line is out of view.

8. (Previously Presented) The method according to claim 1, wherein said determining step comprises the step of constructing the graphics guide as a line, and said rendering step comprises the step of modulating the transparency of portions of the line so that at least a portion of the instrument is substantially unobstructed when viewed through the portions of the line.

9. (Previously Presented) The method according to claim 1, wherein said determining step comprises the step of constructing the graphics guide as a line, and said rendering step comprises the step of modulating the transparency of portions of the line with respect to time and space so that at least a portion of the instrument is substantially unobstructed when viewed through the portions of the line during pre-defined time intervals.

10. (Previously Presented) The method according to claim 1, wherein said determining step comprises the step of constructing the graphics guide as a cylinder, and said rendering step comprises the step of modulating the transparency of the cylinder with respect to time so that the cylinder repeatedly fades in and out of view to provide a substantially unobstructed view of the instrument when the cylinder is out of view.

11. (Previously Presented) The method according to claim 1, wherein said determining step comprises the step of constructing the graphics guide as a cylinder, and said rendering step comprises the step of modulating the transparency of portions of the cylinder so that at least a portion of the instrument is substantially unobstructed when viewed through the portions of the cylinder.

12. (Previously Presented) The method according to claim 1, wherein said determining step comprises the step of constructing the graphics guide as a cylinder, and said rendering step comprises the step of modulating the transparency of portions of the cylinder with respect to time and space so that at least a portion of the instrument is substantially unobstructed when viewed through the portions of the cylinder during pre-defined time intervals.

13. (Currently Amended) An apparatus for augmented reality guided instrument positioning, comprising:

a video camera providing a real view of an environment including an instrument;

a graphics guide generator for identifying a preferred path for positioning said instrument and generating a graphics guide for marking the preferred path ~~positioning an instrument;~~ and

a rendering device for augmenting the real view with a rendering of the graphics guide such that ~~a transparency of~~ at least one portion of the graphics guide is transparent with respect to other portions of the graphics guide to provide a substantially unobstructed view through the at least one portion of the graphics guide to at least a portion of the instrument; modulated in and out of an augmented view repeatedly over a predefined time interval, independent of a change in a view of the graphics guide
an alignment device for aligning the instrument to the graphics guide so that the instrument appears in a same location as the graphics guide in the augmented view, and when properly aligned, at least a portion of the instrument is visible through the at least one transparent portion of the graphics guide; and
an insertion device for inserting the instrument in the graphics guide..

14. (Currently Amended) The apparatus according to claim 13, wherein ~~said rendering device varies a transparency of the at least one~~ said rendering device includes a modulation of the graphics guide's transparency along the length of the graphics guide, so that a plurality of portions of the graphics guide appear transparent with respect to other portions of the graphics guide along the length of the graphics guide to provide a substantially unobstructed view through the ~~at least one~~ plurality of transparent portions of the graphics guide to a plurality of portions of the instrument once the instrument has been correctly aligned with the graphics guide.

15. (Previously Presented) The apparatus according to claim 13, wherein said rendering device varies the transparency of the at least one portion of the graphics guide during pre-defined time intervals to provide a substantially unobstructed view through the at least one portion of the graphics guide to at least a portion of the instrument during the pre-defined time intervals.

16. (Previously Presented) The apparatus according to claim 13, wherein said rendering device sequentially varies the transparency of each of a plurality of portions of the graphics guide during at least one pre-defined time interval to provide a substantially unobstructed view through each of the plurality of portions to at least a portion of the

instrument as the transparency of each of the plurality of portions is varied during the at least one pre-defined time interval.

17. (Canceled).

18. (Previously Presented) The apparatus according to claim 13, wherein said rendering device varies the transparency of the at least one portion of the graphics guide such that the at least one portion repeatedly switches between transparent and less transparent.

19. (Previously Presented) The apparatus according to claim 13, wherein said graphics guide generator constructs the graphics guide as a line, and said rendering device modulates the transparency of the line with respect to time so that the line repeatedly fades in and out of view to provide a substantially unobstructed view of the instrument when the line is out of view.

20. (Previously Presented) The apparatus according to claim 13, wherein said determining device constructs the graphics guide as a line, and said rendering device modulates the transparency of portions of the line so that at least a portion of the instrument is substantially unobstructed when viewed through the portions of the line.

21. (Previously Presented) The apparatus according to claim 13, wherein said graphics guide generator constructs the graphics guide as a line, and said rendering device modulates the transparency of portions of the line with respect to time and space so that at least a portion of the instrument is substantially unobstructed when viewed through the portions of the line during pre-defined time intervals.

22. (Previously Presented) The apparatus according to claim 13, wherein said graphics guide generator constructs the graphics guide as a cylinder, and said rendering device modulates the transparency of the cylinder with respect to time so that the cylinder repeatedly fades in and out of view to provide a substantially unobstructed view of the instrument when the cylinder is out of view.

23. (Previously Presented) The apparatus according to claim 13, wherein said graphics guide generator constructs the graphics guide as a cylinder, and said rendering device modulates the transparency of portions of the cylinder so that at least a portion of the instrument is substantially unobstructed when viewed through the portions of the cylinder.

24. (Previously Presented) The apparatus according to claim 13, wherein said graphics guide generator constructs the graphics guide as a cylinder, and said rendering device modulates the transparency of portions of the cylinder with respect to time and space so that at least a portion of the instrument is substantially unobstructed when viewed through the portions of the cylinder during pre-defined time intervals.

25. (Currently Amended) A method for augmented reality guided instrument positioning, comprising the steps of:

displaying a real camera view of an environment including an ~~endoscopic~~ instrument;

determining a ~~virtual view~~ preferred path of the ~~endoscopic~~ instrument in the environment;

marking the preferred path with a ~~determining a~~ graphics guide, the graphics guide indicating a predetermined position to which the ~~endoscopic~~ instrument is alignable; and

augmenting the real camera view with a rendering of ~~a the~~ virtual view of the ~~endoscopic instrument and the~~ graphics guide such that ~~an appearance of~~ at least one portion of the graphics guide is transparent ~~modulated with respect to at least one of space and time, wherein said rendering comprises varying a transparency of the at least one portion of the graphics guide with respect to other portions of the graphics guide to provide a substantially unobstructed view through the at least one portion of the graphics guide to at least a a portion of the virtual view of the endoscopic instrument;~~

aligning the instrument to the graphics guide so that the instrument appears in a same location as the graphics guide in the augmented view, and when properly aligned,

the instrument is visible through the at least one transparent portion of the graphics guide;
and

inserting the instrument in the graphics guide.

26. (Canceled).

27. (Canceled).

28. (New) The method according to claim 1, where the transparency of the graphics guide is modulated with respect to time.